

MINI LAZER DOWNLIGHT

Drawing CODE: JL50x

Product CODE: ISH-JL50x

BRAND:ARCHLUX

Product description:

The ISH-JL50X Series consists of compact architectural mini laser downlights designed for precision accent lighting applications. Featuring premium USA CREE LED technology, narrow beam optics, and high-quality aluminum construction, the series delivers focused illumination with excellent visual comfort and color performance.

The range includes 2W, 4W, and 10W models to accommodate various lighting requirements while maintaining a consistent design language suitable for residential, retail, hospitality, and display lighting projects.

Technical Specifications:

- USA CREE LED Technology
 - Narrow 15° Beam Angle
 - Warm White 3000K
 - Compact Architectural Design
- High CRI Performance
 - Aluminum Construction
 - Recessed Installation
 - Suitable for Accent & Display Lighting

Series Specifications:

Parameter	Specification
Series	ISH-JL50X
LED Type	USA CREE Chips
Input Voltage	100–240VAC
Color Temperature	3000K
CRI	90
Beam Angle	15°
Reflector	Anti-Glare Black
Installation	Recessed
Housing Material	Aluminum

ARCHLUX®

JL SERIES

RECESSED LED DOWNLIGHT



JL101



JL202



JL505



MINI LAZER DOWNLIGHT

Drawing CODE: JL50x

Product CODE: ISH-JL50x

BRAND:ARCHLUX

Available Models:

➤ MINI LAZER DOWNLIGHT 2W

Parameter	Specification
Model	ISH-JL501
Power Consumption	2W
LED Type	USA CREE Chip
Luminous Output	200 lm
Fixture Dimensions	45 × 45 × 49 mm



➤ MINI LAZER DOWNLIGHT 4W

Parameter	Specification
Model	ISH-JL502
Power Consumption	4W
LED Type	USA CREE Chip
Luminous Output	400 lm
Fixture Dimensions	75 × 45 × 50 mm



➤ LINEAR MINI DOWNLIGHT NARROW BEAM

Parameter	Specification
Model	ISH-JL505
Power Consumption	10W
LED Type	USA CREE Chip
Luminous Output	1000 lm
Fixture Dimensions	146 × 45 × 43 mm

